



The information contained in this document may alter at any time without prior notice. No part of this document may be copied or otherwise duplicated without prior written consent. All rights reserved.

WilTec Wildanger Technik GmbH cannot be held liable for any possible mistakes in this operating manual, nor in the diagrams and illustrations shown.

If you have found an error or wish to suggest an improvement, we look forward to hearing from you.

Send us an e-mail to:

E-mail: [service@wiltec.info](mailto:service@wiltec.info)

Tel: +49 2403 55592-0

Fax: +49 2403 55592-15

Our postal address is:

WilTec Wildanger Technik GmbH  
Königsbenden 12  
52249 Eschweiler – Germany

## Using safety equipment

- During installation and use, always wear safety gloves.
- Also wear other suitable protective equipment parts.

## Manoeuvring via the jockey wheel

Manoeuvring via the jockey wheel might lead to damage of the wheel on an unsuitable lane or with a high load.

- Only perform manoeuvring without load and on a level surface.
- Only perform manoeuvring in coupled condition and with the jockey wheel retracted.

## Blocking against rolling away caused by jockey wheel

The jockey wheel is not suitable as safeguard against rolling away. A trailer blocked by the jockey wheel is to be considered as unblocked. The trailer might roll into the traffic by itself and in an uncontrolled manner. Persons might be injured. Objects might be damaged.

- Block the wheels of your trailer with wedges.

## Loose screw connections

Screw connections might loosen over time.

- After the first installation, after the 50 first kilometres of use, if the screw connections are tight.
- Furthermore, control the tightness of the screw connection on a regular basis.

## Driving with jockey wheel retracted

The jockey wheel can only be used with the vehicle standing. When kept extended during a ride, the jockey wheel might go off in part or completely, hinder the traffic, and cause damages of the trailer and vehicle. Persons might be injured or even killed.

- Control the tightness of the crank.
- Make sure that the jockey wheel is wound up completely.

## Securing the load on the jockey wheel

The jockey wheel is not suitable as safeguard against rolling away. Load fixed to the jockey wheel is to be considered as not secured. The trailer, vehicle, and load might be damaged. Non secured load might have an influence on the stability of the vehicle and trailer by own movements. There is a risk of sideslipping.

- Use the fixation points found on the trailer.
- Use suitable means of securing a load.
- Arrange the load so that the transport will be trouble-free.

## Technical modifications

The trailer has all necessary bores factory-made for connecting a jockey wheel. Additional bores deviating from the licence of the trailer will void this licence.