

User's manual

Oil Drainer Cart

61709



Illustration similar, may vary depending on model

Read and follow the operating instructions and safety information before using for the first time.

Technical changes reserved!

Illustrations, functional steps, and technical data may deviate insignificantly due to continuous further developments.

Updating the documentation

If you have suggestions for improvement or have found any irregularities, please contact us.



The information contained in this document may alter at any time without prior notice. No part of this document may be copied or otherwise duplicated without prior written consent. All rights reserved. WilTec Wildanger Technik GmbH cannot be held liable for any possible mistakes in this operating manual, nor in the diagrams and illustrations shown.

Although WilTec Wildanger Technik GmbH has made every possible effort to ensure that this operating manual is complete, accurate, and up-to-date, errors cannot be ruled out entirely.

If you have found an error or wish to suggest an improvement, we look forward to hearing from you. Send us an e-mail to:

service@wiltec.info

or use our contact form:

<https://www.wiltec.de/contacts/>

The most recent version of this manual in several languages can be found in our online shop:

<https://www.wiltec.de/docsearch>

Our postal address is:

WilTec Wildanger Technik GmbH
Königsbenden 12
52249 Eschweiler – Germany

To return your goods for exchange, repair, or other purposes, please use the following address. Attention! To allow for a trouble-free complaint or return, it is important to contact our customer service team before returning your goods.

Retourenabteilung
WilTec Wildanger Technik GmbH
Königsbenden 28
52249 Eschweiler – Germany

E-mail: **service@wiltec.info**

Tel: +49 2403 55592-0

Fax: +49 2403 55592-15




Introduction

Thank you for choosing to purchase this quality product. To minimise the risk of injury, we ask you to always take some basic safety precautions when using this product. Please read this operating manual carefully and make sure that you understand it.

Keep these operation instructions in a safe place.

The oil drainer cart is ideal for collection of used oil and other car liquids. The adjustable height of the oil funnel allows the user to vary the distance between the oil sump of the vehicle and the funnel to minimise oil spillage. There is no used oil container included in the scope of delivery.

Safety instructions

- Read and understand all instructions. Disobeying the instructions stated below might lead to electric shocks, fire, and/or severe injuries.
- Obey all precautionary measures, information and instructions found in this manual. Always use the device with caution to minimise risk of injuries.
- Only use the oil drainer cart in a suitable work area. Keep the work area clean and tidy, remove all foreign matter, and ensure sufficient illumination.
- Keep children and unauthorised persons away from your working area.
- During use, wear a suitable safety equipment as protective gloves, protective clothes, or anti-slip shoes.
- Avoid excessive contact with used oils. Frequent or long-term contact can cause skin irritations and diseases.
-  Immediately remove spilled oil. **Slip danger!**
- Do not expose the device to rain or splash water.
- Keep the device in a dry, clean, and neat condition to allow the best and safest possible operation.
- Place the device on a level, clean, and dry surface. Make sure as well that the surface can carry the load weight.
- Do not drain the oil by force. Using the device will be better and safer if used as intended. Plan your work and use the suitable tools for it.
- Make sure that all connectors are tight. If the connectors are untight, the device should not be used.
- Never leave the cart filled with oil without supervision.
- Place the oil drainer cart so that it cannot provoke any danger when moving or storing it or when draining the oil.
- When not in use, the oil drainer cart must be stored at a dry and safe place and out of children's reach. Before storage and re-use, check it for proper condition.
- Absolutely respect the local regulations concerning the elimination of used oils.



Caution! Under no circumstances allow escaping liquids to pollute the environment!

Assembly

1. Connect the hopper **(1)** with the height-adjustable upper tube **(2)**. Fix the lower tube **(2)** with the help of the fastener **(3)**.
2. Fix the tool rack **(4)** to the lower tube **(5)**, then insert the lower tube **(5)** into the oil tank **(8)**. Secure the tube **(5)** with the fixing screw **(6)**.

Components



No	Name	Qty.
1	Hopper and filter	1
2	Upper tube	1
3	Fastener	1
4	Tool rack	1
5	Lower tube	1
6	Fixing screw	1
7	Drain cap	1
8	Oil tank	1
9	Wheel	4

Operation

1. Place the mobile oil drain cart beneath the device that will be emptied.
2. Place the hopper (1) beneath the drain valve or vent of the device.
3. After draining, re-lower the hopper (1) before removing the oil drain device.

Emptying the oil drain device

1. Remove the hopper (1), upper tube (2), and lower tube (5) from the oil tank (8).
2. Place the drain hose of a hand pump (not included) into the oil tank (8) to pump down the used oil.

Maintenance

- Clean the filter of the hopper if necessary.
- Clean the inside of the tank on a regular term.

Important Note: Reproduction and any commercial use (of parts) of this operating manual, requires a written permission of WilTec Wildanger Technik GmbH.