wiltec

Safety instructions

- 1. Check the wheel chocks for signs of wear or damage before each use. Cracks or deformations can impair functionality and should be avoided for safety reasons.
- 2. Place the wheel chocks firmly and securely under the tyres. They should be used on a solid and level surface to prevent slipping or rolling away.
- 3. Use wheel chocks on surfaces that provide sufficient grip. Avoid smooth or wet surfaces that could promote slippage of the chocks.
- 4. Always use wheel chocks when the vehicle is parked, especially on slopes. This prevents the vehicle from moving unexpectedly.
- 5. When wishing to use your vehicle, remove the wheel chocks with car to ensure that the vehicle does not start moving on its own. Check the surroundings before removing the chocks.
- 6. Store the wheel chocks in a dry, clean place to prevent corrosion or damage. Ensure that they are easily accessible when needed.
- 7. Wheel chocks provide additional safety but should never be used as a substitute for applying the parking brake.
- 8. Regularly check the condition of your wheel chocks. Replace them immediately if you detect signs of wear or damage.
- 9. Always wear appropriate safety gear such as gloves and sturdy footwear when applying wheel chocks.

Parts list

N⁰	Name	Illustration	Qty.
1	Screw		8
2	Nut		8
3	Wheel chock		2
4	Holder		2

